

PRODUCT DESCRIPTION

Professional one-component, neutral cure, silicone sealant. Specifically developed for the sealing of different materials such as PVC-U, glass, facades, natural stones, marbles, granites, glazed surfaces and brickwork. High adhesive power with a flexible water tight seal, product does not require primers. Due to its neutral cure formulation, product does not stain, bleed or mark natural stone surfaces. Highly recommended for caulking and sealing applications of between marble, stone, windows and doors.

APPLICATION SURFACES

Marbles, granites, agglomerates, ceramics, cement, glass, stainless steel, aluminium, wood and compensata.

CHEMICAL AND PHYSICAL PROPERTIES

ASPECT :	Thixotropic paste
COLOUR:	See available colours
ODOUR	Odourless
SPECIFIC WEIGHT @ 20°C	0,99 +/- 0,05 g/cm ³
SOLUBILITY ':	Insoluble
PH:	N.A.
STORED @ 20°C	12 months in original packaging



HOW TO USE

ALWAYS TEST PRODUCT FIRST following below indications, before proceeding with complete product application. Ensure that surfaces to be treated are completely clean, free of dirt, dust, grime and surface incrustations.

Manual:

1. Ensure that surfaces to be sealed are clean, dry, sound and free from dirt and grime.
2. Mask off areas with tape to prevent contamination of surrounding surfaces. No primer is required. (if needed use MARMO PRIM)
3. Apply product using traditional cartridge silicone gun. The joint should be tooled within 5minutes of application leaving a smooth finish.

APPLICATION TOOLS

Silicone sealant mastic gun

INDICATED COVERAGE

The coverage depends on the dimension of joint:

Dimension of joint (mm)	Consumption per lineal meter	Lineal meter per cartridge
3x3	20 ml	15
5x5	32 ml	12
6x6	40 ml	7,5
10x10	100 ml	3

COLOUR CHART

CODE	COLOUR	CONTENT	PCS PER BOX
205SMSITR0300	Transparent	310 ML	24
205MSIBI0300	White	310 ML	24
205MSIPA0300	Beige	310 ML	24
205MSIGR0300	Grey	310 ML	24
205MSINE0300	Black	310 ML	24

ATTENTION: Read completely the product label before proceeding with product use. Maintain product in its original container/packaging. Do not disperse packaging in the environment and dispose of separately in accordance with local regulations. Keep out of the reach of children. Always test product first on a small hidden area so to verify final results and product compatibility with material. Product may darken and change the original colour on certain materials. Product does not protect from acid-based substances. While using the product wear indicated protective PPE and clothing and read completely the safety data sheet.

Disclaimer: the present information supersedes and replaces all previous versions. All data indicated in this document are the results of tests and experiments carried out in our laboratories and through reliable operators within the stone business and have to be considered reliable. However, because of the many external and surrounding factors which can influence the final results, the information here reported does not constitute an implicit or a formal guarantee. The end user will undertake the full responsibility in the usage of the product, making sure to test first the product and to experiment with the product as a preventive measure so to understand its full and final characteristics. Bellinzoni has to right to modify any information mentioned on this document, at any time and without notice. Bellinzoni is the sole owner of all trademarks and logos indicated in this document and to copy or modify in part without permission can infringe property rights. Bellinzoni will not be held responsible for its incorrect use and will follow legal percussions as of current law.