

ANTI SEEPAGE TREATMENT FOR TILED AND NATURAL STONE SURFACES

Solvent-based, consolidating, anti-seepage protective treatment. Protects micro hairline cracks, preventing water seepage while strengthening the material. Maintains surface breathability and is UV-resistant.

SURFACES

Product is recommended for marbles, granites, natural stone, cement, terracotta, clinker and gres porcelain.

FEATURES

Dual action solution, protecting and consolidating surfaces. Prevents water seepage from penetrating through micro hairline cracks (from 0.5 µm to 1 mm) into below substrate and consequently avoiding any serious structural issues. Avoids the formation of mould and surface efflorescence.

HOW TO USE

Remove all surface debris, dust and previous applied treatments. Surfaces must be dry and clean before application. **For preparation of surface after installation:** proceed to use B 27 EXXTRA (Cod. P012) as indicated on technical data. **For an initial deep clean of surface:** proceed to use B-XTREME HD CLEANER (Cod. P061) as indicated on technical data. Product ready for use. Apply a coat of product uniformly using a brush, microfiber cloth, wax applicator or roller to surfaces. Allow product to be completely absorbed for approximately 3-5 minutes before applying a second coat at right angles to the first. Allow product to penetrate into all surface cracks and spaces. Remove eventual excess product or residues before product completely dries using a cotton cloth or with dry wax applicator. On porous surfaces, apply product until complete saturation. Treated surfaces can be used after 12 hours from initial application. Allow 24 hours for full surface protection.

ADVANTAGES

Protects surfaces without leaving surface residues or plastic effects. Non yellowing and UV resistant. Deep penetrating, strengthens the material.

ADVICE

Do not apply if rain is forecasted within the next 24 hours from application. Do not apply to damp surfaces or areas with high moisture content. Avoid product stagnating.



CHEMICAL PROPERTIES

APPEARANCE: Liquid
 COLOUR: Colourless
 ODOUR: Characteristic
 SOLUBILITY: Insoluble
 PH:

COVERAGE FOR LITRE

Terracotta and stone: Approximately 10-15m²
 Gres porcelain and clinker: Approx. 30m²

(Product coverage may vary depending on type and porosity of material where used)

PACKAGING

| Code | Content | Pc./Carton |
|------------|---------|------------|
| P125BTR02L | 250ml | 12 |
| P125BTR10L | 1 lt | 6 |
| P125BTR50L | 5 lt | 4 |

for information: www.bellinzoni.com

MADE IN ITALY



ATTENTION:

Carefully read the recommendations printed on the label. Always test before use. Do not dispose of the container in the environment after use, follow the disposal information indicated on the label. Keep out of reach of children. The product has anti-stain properties but does not protect surfaces from acids. Check the actual resistance of the material to the product on a hidden portion of the surface to be treated. When using the product, use suitable PPE and consult the safety data sheet.

This document replaces and cancels the previous ones. The information contained in this document is the result of accurate tests and experiences carried out in our laboratories and is to be considered reliable, however, given the complexity of the materials and the variability of the conditions of use, the user is advised to perform tests on a hidden portion of the surface to be treated before the application of the product. Bellinzoni reserves the right to make changes at any time without prior notice. The trademarks and logos are the exclusive property of Bellinzoni s.r.l. copying or modifying all or part of what is contained in this document is prohibited, exempts the Bellinzoni company from any liability and will be prosecuted by law.