

WOOD FLOOR WAX (wax for wood floors)

Self-polishing, high coverage floor wax for parquet floors.



CHEMICAL PROPERTIES

APPEARANCE: Liquid
COLOUR: White
ODOUR: Sandalwood
SOLUBILITY: Mixable in water
PH: 8,50 ± 0,50

COVERAGE FOR LITRE

Natural varnished parquet: approx. 50-70 m²
(Product coverage may vary depending on type and porosity of material where used)

ontent	D (O .
JIICOIIC	Pc./Carton
t	6
lt .	4
	•

information:

www.bellinzoni.com

MADE IN ITALY • 0 •



ATTENTION:

SURFACES

Product can be used on all varnished parquet floors, laminates, LVT and hardwood floors in Doussié, oak, iroko, fir and walnut.

FEATURES

High gloss, "mono-coat", metallized floor polish for a durable, high-performance finish of parquet floors. Products resists to high foot traffic and to the daily use of general detergents and cleaning products, while maintaining the natural beauty and colours of the parquet floor. Thanks to its self-polishing characteristics, product gives a warm, long lasting polished finish to surfaces. Self-crosslinking properties even at low temperatures, thanks to the action of auto-plasticisers contained in product. Renews worn down parquet surfaces giving a uniform and rejuvenating gloss and look. Cleaned surfaces maintain a long-lasting pleasant perfume of sandalwood when used. Treated surfaces are maintained with ease with neutral detergents, due to its "easy clean "effect.

HOW TO USE

Ready for use. Apply to dry and clean surfaces. Remove all surface debris, dust and previous applied waxes using B-SUPER CLEANER.

Apply a small amount of product evenly at a time using a microfiber cloth, lambswool wax applicator or cotton rag to surface. Apply product to small sections at a time, avoiding over lapping product. Maintain one direction when applying product. Do not apply to opposite directions (criss-cross). Allow a minimum of 60 minutes for curing before resuming normal use of treated areas.

ADVANTAGES

Fast drying and self-crosslinking formulation. High gloss finish. Resistant to high foot traffic. Intense perfume.

ADVICE

Remove all previous waxes from surface. Avoid over-applying product, avoid surface bubbles and foam build-up. Do not walk on treated surfaces when wet and maintain surface dust free until product has completely dried. Do not use on damp or humid surfaces or in water prone areas such as showers and bathrooms. For the on-going maintenance, use B-LEM3 EXXTRA WD as indicated on the TDS for the daily cleaning of treated surfaces.

Carefully read the recommendations printed on the label. Always test before use. Do not dispose of the container in the environment after use, follow the disposal information indicated on the label. Keep out of reach of children. The product has anti-stain properties but does not protect surfaces from acids. Check the actual resistance of the material to the product on a hidden portion of the surface to be treated. When using the product, use suitable PPE and consult the safety data sheet.